## **EDGE8™** Housing

1 U, slide out, holds up to 12 EDGE8 modules or adapter panels



EDGE8™ solutions are high-density preterminated optical cabling solutions with optimised design for base-8 fibre applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds and changes.

### **Features and Benefits**

# Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8 modules and panels

#### **Key identifiers**

EDGE8 printed on housing for easy identification as a Base-8 component

# Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimised finger access to connectors combined with industry leading port density

#### Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

### Removable top covers on the 1 U and 2 U housings Provides easier access to modules and panels

#### Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

# Ultra high port concentration with MTP Base-8 system in 1 U housing (slide out)

48 LC duplex ports (96 fibre) or 48 MTP ports (384 fibre)





# **EDGE8™** Housing

1 U, slide out, holds up to 12 EDGE8 modules or adapter panels



### **Specifications**

General Specifications	
Application	Data Centre
Product type	Fibre Optic Hardware
Mounting type	Rack 19"

Design - Hardware	
Height unit	1U
Housing colour	Silver
Housing type	Pretium EDGE®
Number of Panels per Housing	12

Mechanical Characteristics	
Dimensions (W x D x H)	432 mm x 561 mm x 44 mm (17 in x 22.1 in x 1.75 in)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

## **Ordering Information**

Part Number	EDGE8-01U
Product Description	EDGE8™ Housing, 1 U, slide out, holds up to 12 EDGE8 modules or adapter panels

### **Shipping Information**

Units per delivery	1/1
Packaging Dimensions (W x D x H)	584 mm x 673 mm x 191 mm (23 in x 26.5 in x 7.5 in)
Shipping Weight	6.8 kg (15 lb)



## **EDGE8™** Housing

1 U, slide out, holds up to 12 EDGE8 modules or adapter panels



**Notes** 



Corning Optical Communications GmbH & Co. KG  $\cdot$  Leipziger Strasse 121  $\cdot$  10117 Berlin, GERMANY 00 800 2676 4641  $\cdot$  FAX: +49 30 5303 2335  $\cdot$  www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.

