## **EDGE8™** Housing

2 U, holds up to 36 EDGE8 modules or adapter panels



EDGE8™ solutions are high-density preterminated optical cabling solutions with optimised design for base-8 fibre applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds and changes.

### Features and Benefits

## Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8 modules and panels

#### **Key identifiers**

EDGE8 printed on housing for easy identification as a Base-8 component

## Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimised finger access to connectors combined with industry leading port density

#### Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

#### Removable top covers on the 1 U and 2 U housings Provides easier access to modules and panels

#### Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

## Ultra high port concentration with MTP Base-8 system in 2 U housing

144 LC duplex ports (288 fibre) or 144 MTP ports (1152 fibre)







# **EDGE8™** Housing

2 U, holds up to 36 EDGE8 modules or adapter panels



### **Specifications**

General Specifications	
Application	Data Centre
Product type	Fibre Optic Hardware
Mounting type	Rack 19"

Design - Hardware	
Height unit	2U
Housing colour	Silver
Housing type	Pretium EDGE®
Number of Panels per Housing	36

Mechanical Characteristics	
Dimensions (W x D x H)	432 mm x 561 mm x 88 mm (17.0 in x 22.1 in x 3.5 in)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/ EG

### **Ordering Information**

Part Number	EDGE8-02U
Product Description	EDGE8™ Housing, 2 U, holds up to 36 EDGE8 modules or adapter panels

### **Shipping Information**

Units per delivery	1/1
Packaging Dimensions (W x D x H)	578 mm x 667 mm x 241 mm (22.75 in x 26.25 in x 9.5 in)
Shipping Weight	10.4 kg (23 lb)



## **EDGE8™** Housing

2 U, holds up to 36 EDGE8 modules or adapter panels



**Notes** 



Corning Optical Communications GmbH & Co. KG  $\cdot$  Leipziger Strasse 121  $\cdot$  10117 Berlin, GERMANY 00 800 2676 4641  $\cdot$  FAX: +49 30 5303 2335  $\cdot$  www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.

