

EDGE8™ Housing

4 U, holds up to 72 EDGE8 modules or adapter panels

CORNING

EDGE8™ solutions are high-density preterminated optical cabling solutions with optimised design for base-8 fibre applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds and changes.

Features and Benefits

Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8 modules and panels

Key identifiers

EDGE8 printed on housing for easy identification as a Base-8 component

Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimised finger access to connectors combined with industry leading port density

Integrated strain-relief plate can rotate 90°

Allows for rear cable entry direction, as well as the traditional side cable entry

Removable top covers on the 1 U and 2 U housings

Provides easier access to modules and panels

Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

Ultra high port concentration with MTP Base-8 system in 4 U housing

288 LC duplex ports (576 fibre) or 288 MTP ports (2304 fibre)



EDGE8-04U Front View | Photo REN473



Part Number: EDGE8-04U

EDGE8™ Housing

4 U, holds up to 72 EDGE8 modules or adapter panels



Specifications

General Specifications

Application	Data Centre
Product type	Fibre Optic Hardware
Mounting type	Rack 19"

Design - Hardware

Height unit	4U
Housing colour	Silver
Housing type	Pretium EDGE®
Number of Panels per Housing	72

Mechanical Characteristics

Dimensions (W x D x H)	432 mm x 561 mm x 177 mm (17.0 in x 22.1 in x 7.0 in)
------------------------	---

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	EDGE8-04U
Product Description	EDGE8™ Housing, 4 U, holds up to 72 EDGE8 modules or adapter panels

Shipping Information

Units per delivery	1/1
Packaging Dimensions (W x D x H)	578 mm x 667 mm x 327 mm (22.75 in x 26.25 in x 12.9 in)
Shipping Weight	16.5 kg (36 lb)

EDGE8™ Housing

4 U, holds up to 72 EDGE8 modules or adapter panels

The CORNING logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered inside.

Notes



**Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea**

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2015 Corning Optical Communications. All rights reserved.